|| Parallels[®]

Netboot image is not available as a boot option.

• Parallels Device Management

Symptoms

I have created a **NBI** file and converted it to a **WIM** file and created a **task sequence** and deployed the **task sequence** to a collection of **Macs**. The problem is that the **NetBoot image** option is not appearing as a boot option on the target Macs.

Please check `pma_isv_netboot_service.log' for the following errors:

```
W /PmaUtils:32916:556c/ Could not construct WMI namespace: host = '', site code = '
D /pma_netboot_service:32916:556c/ SMS Provider:
D /pma_netboot_service:32916:556c/ Starting DistributionAgent...
D /pma_netboot_service:32916:556c/ DistributionAgent has started
D /pma_netboot_service:32916:556c/ Starting BsdpServer...
D /pma_netboot_service:32916:556c/ Listening on \\.\pipe\pma_netboot_service.pipe
D /pma_netboot_service:32916:556c/ BsdpServer has started
I /pma_netboot_service:32916:556c/ Distribution Point NAL path is ''.
I /pma_netboot_service:32916:37fc/ Unable to fetch data (Unable to read DP NAL path. Check that ac
D /pma_netboot_service:32916:556c/ Stop service
```

Cause

Check C: \Windows\Logs for pma_netboot_config.log.

If there is no such file it means that **NetBoot Server Configuration Utility** has failed to configure or has not been run yet.

NOTE: In case log file persists, please follow this article: http://kb.parallels.com/en/122853

Resolution

Run NetBoot Server Configuration Utility, proceed with configuring and check the issue.

© 2024 Parallels International GmbH. All rights reserved. Parallels, the Parallels logo and Parallels Desktop are registered trademarks of Parallels International GmbH. All other product and company names and logos are the trademarks or registered trademarks of their respective owners.