

Parallels Mac Management does not push clients after Active <u>Directory discovery</u>

• Parallels Device Management 4.5

Symptoms

Parallels Mac Management does not push clients after Active Directory discovery

Information

To successfully install Parallels Mac Management client using **Client Push** feature the following requirements should be met:

- 1. Mac should be joined to Active Directory.
- 2. Active Directory System discovery should be launched.
- 3. Found resource should **not** have any client isntalled:
- 4. SCCM should assign **Operating System Name** to found resource. Note that Operating System Name should contain **Mac OS X** or **macOS** substrings:

If **Operating System Name** is not assigned or does not have **Mac OS X** or **macOS** substrings, then Parallels Mac Management cannot confirm that found resource is a Mac.

5. SCCM should assign **Configuration Manager Resident Sites** to found resource:

Note in most cases **Configuration Manager Resident Site** is not assigned, because of SCCM Boundaries misconfiguration.

If **Configuration Manager Resident Site** is not assigned, then Parallels Mac Management cannot check what SCCM Site resource belongs to.

- 6. Client Push should be enabled:
 - ♦ navigate to SCCM Overview > Administration > Site Configuration > Sites > right-click required Site > Parallels Mac Client Push Installation.
 - ♦ in General tab enable Automatic site-wide client push installation:
 - in **Accounts** tab accounts that have Administrator permissions on a Mac should be added:
- 7. SSH port should be opened on a Mac

Parallels Mac Management Proxy checks for devices that are available for client push every 10 minutes.

Logs

Here is an example of successful client push (%SystemRoot%\Logs\pma_isv_proxy_service.log):

```
05-09 15:08:21.344 D /ClientPush:6592:154c/ Utility path: 'C:/Program Files (x86)/Parallels/Paralle 05-09 15:08:21.357 D /LocalIpc:6592:2a40/ Unnamed connection is found: 0x035B84C0 05-09 15:08:21.357 D /LocalIpc:6592:2a40/ connectionName: pmm_clientpush 05-09 15:08:21.357 D /LocalIpc:6592:2a40/ Client 'pmm_clientpush' connected to server with code: 05-09 15:08:21.357 D /ClientPush:6592:2a40/ IPC Connected: pmm_clientpush 05-09 15:08:21.366 D /PrlCommonUtils:6592:154c/ Started 'C:/Program Files (x86)/Parallels/Parallels-05-09 15:08:43.459 D /ClientPushManager:6592:154c/ Use new SMS ID: 75d90a8a-887a-784d-a112-e2c7a48: 05-09 15:08:46.804 D /pma_isv_proxy_service:6592:1170/ Got file request from '10.2.0.57' for /files-05-09 15:08:46.806 D /pma_isv_proxy_service:6592:1170/ Sent agent package file 'C:/Program Files (s05-09 15:09:02.757 D /ClientPushManager:6592:154c/ Job '{886076a4-b1c4-824a-9383-b8202d586b1a}' fine 05-09 15:09:04.614 I /ClientPushManager:6592:154c/ No more jobs in queue. Stop install manager. 05-09 15:09:04.614 I /ClientPushManager:6592:154c/ Stopping Client Push Installation utility...
```

© 2024 Parallels International GmbH. All rights reserved. Parallels, the Parallels logo and Parallels Desktop are registered trademarks of Parallels International GmbH. All other product and company names and logos are the trademarks or registered trademarks of their respective owners.