

Disabling Memshell hooking for specific applications

- Parallels Remote Application Server 18.0
- Parallels Remote Application Server 19.1
- Parallels Remote Application Server 18.2
- Parallels Remote Application Server 18.3
- Parallels Remote Application Server 19.0
- Parallels Remote Application Server 18.1

To make a published application ignore any Memshell hooking, one should follow the steps below:

- 1. Open registry editor on the RDS host from which the application in question is published.
- 2. Navigate to the following location:

For 64-bit applications: HKEY_LOCAL_MACHINE\SOFTWARE\WOW6432Node\Parallels\
For 32-bit applications: HKEY_LOCAL_MACHINE\SOFTWARE\Parallels\

- 3. Create a new key called Memshell
- 4. Within a created Memshell key create a String named IgnoreHookApplications
- 5. **IgnoreHookApplications** value should match the **exact name of executable file** of application in question (*.exe file). Please refer to screenshot below:

To disable Memshell hook for several applications specify all executables separated by a **semicolon**:

Note: Applications listed in this string will completely ignore any other hooking settings, thus please use it on a staging environment first to ensure it is not affecting critical functionality.

© 2024 Parallels International GmbH. All rights reserved. Parallels, the Parallels logo and Parallels Desktop are registered trademarks of Parallels International GmbH. All other product and company names and logos are the trademarks or registered trademarks of their respective owners.