



How to change a virtual machine's Hardware UUID

- Parallels Desktop for Mac Standard Edition
- Parallels Desktop for Mac App Store Edition
- Parallels Desktop for Mac Business Edition

Question

How can I change my virtual machine's Hardware UUID?

Information

Please note that it is currently not possible to set a specific Hardware UUID to a virtual machine, but you can make Parallels Desktop generate a random new one by performing the following steps:

1. Make sure that the virtual machine is shut down. If it is in a suspended state, please run it and then shut down (Actions > Shut Down).
2. Locate the virtual machine file: click on **Parallels icon || > Control Center** > right-click on the virtual machine > **Show in Finder**.
3. Right-click the pvm file > **Show package contents**.
4. Right-click on the config.pvs > **Open with > TextEdit** > locate a string that looks like:

```
<SourceVmUuid>{1234abcd-12ab-34cd-56ef-54321abcdef7890}</SourceVmUuid>
```

5. Change any digit or letter inside the curly braces.

6. Press Command-S shortcut to save changes.
7. Start the virtual machine.

Once you start the virtual machine, the UUID will be changed.

© 2024 Parallels International GmbH. All rights reserved. Parallels, the Parallels logo and Parallels Desktop are registered trademarks of Parallels International GmbH. All other product and company names and logos are the trademarks or registered trademarks of their respective owners.